

## Viewline Temperature Gauges 12/24 Volt

### Description

Gauge to indicate Coolant-, Engine oil-, Hydraulic-, Gear- and Cylinder temperature.



Picture: Coolant Temperature Gauge

### Features

- \_ LED illumination
- \_ Integrated Warning LED
- \_ Changeable bezels
- \_ Backlit technology
- \_ Antifog and splash protection
- \_ Panel and flush mount possibility



### Concept

Housing	Polycarbonat (PC)
Bezel	PC (black, white) or ABS (chrome); several colors and shapes (see accessories table)
Lens	PMMA; double lens
Dial	backlit, different colors (black, white)
Pointer	backlit, white on black dials; red on white dials
Illumination	backlit Dial: LED amber (605nm) Pointer: LED red (632nm)
Warning LED	red (632nm)
Mounting	Spinlock Nut; locking height 0.5mm – 20mm, Optional Studs and Bracket; locking height 2 – 15mm
Connection	8 pin MQS connector system

Technical Data		
Installation depth	50mm	
Installation diameter	52mm	
Deflection angle	90°	
Operating Voltage	10 – 32 Volt	
Accuracy	< 3.6 angular degrees at 13.0 Volt	
Current consumption	< 140 mA, incl. Warn LED	
Operating temperature	-30°C to +80°C; plated bezels (chrome) -30°C to +70°C	
Storage temperature	-30°C to +80°C for 48h; plated bezels (chrome) -30°C to +70°C	
Temperature shock	Range Transformation time Retention time	-40°C to +85°C; plated bezels (chrome) -40°C to +70°C 10 seconds 2h
Climatic test	Range Rel. Humidity	+25°C to +55°C 95%
EMC in conformity with (Electromagnetic compatibility)	DIN_EN 61000-6-2 DIN_EN 61000-6-3	
Standards	CE ECE – R10	
Vibration	Sinus 2g; 10-500Hz; duration 16h Noise 3g; 10-1000Hz, duration 8h	
Mechanical shock	continuous Single shock Free fall	25g; 6ms; 1Hz 100g; 11ms 1m; 3 times
Chemical resistance against	<ul style="list-style-type: none"> <li>- preservative agent</li> <li>- preservative agent remover</li> <li>- cold cleaner</li> <li>- methylated spirit</li> <li>- interior cleaner</li> <li>- drinks containing caffeine and tannin</li> </ul>	
Nominal position	NL 0 to NL 85 (DIN16257)	
Protection class	according to IEC 60529 Front: IP67 (in nominal position) Rear: IP52 (in nominal position)	
Reverse polarity protection	yes, 5 minute	
Over voltage protection	yes, 1 minute	

## Available Gauges:

No. unpacked *	Dial color	Measurement range outer		Measurement range inner		ISO Symbol	Sensor resistance range
		Min	Max	Min	Max		
A2C53418131	black	20°C	100°C	none	none		287.4 – 22.7 Ohm
A2C53418132	black	40°C	120°C	none	none		287.4 – 22.7 Ohm
A2C53413314	black	40°C	120°C	none	none		287.4 – 22.7 Ohm
A2C53413315	black	40°C	120°C	none	none		287.4 – 22.7 Ohm
A2C53413385	black	40°C	120°C	105°F	250°F		287.4 – 22.7 Ohm
A2C53418133	black	50°C	150°C	none	none		322.8 – 18.6 Ohm
A2C53413389	black	50°C	150°C	none	none		322.8 – 18.6 Ohm
A2C53413400	black	50°C	150°C	none	none		322.8 – 18.6 Ohm
A2C53413404	black	50°C	150°C	120°F	300°F		322.8 – 18.6 Ohm
A2C53418134	black	60°C	200°C	none	none	none	482.5 – 14.3 Ohm
A2C53413351	black	100°F	240°F	none	none		384 - 29 Ohm
A2C53413355	black	105°F	250°F	none	none		287.4 – 22.7 Ohm
A2C53413386	black	105°F	250°F	40°C	120°C		287.4 – 22.7 Ohm
A2C53413401	black	120°F	300°F	none	none		322.8 – 18.6 Ohm
A2C53413405	black	120°F	300°F	50°C	150°C		322.8 – 18.6 Ohm
A2C53418135	black	140°F	400°F	none	none	none	482.5 – 14.3 Ohm
A2C53413382	white	40°C	120°C	none	none		287.4 – 22.7 Ohm
A2C53413387	white	40°C	120°C	105°F	250°F		287.4 – 22.7 Ohm
A2C53413402	white	50°C	150°C	none	none		322.8 – 18.6 Ohm
A2C53413406	white	50°C	150°C	120°F	300°F		322.8 – 18.6 Ohm
A2C53413383	white	100°F	240°F	none	none	<b>WATER</b>	384 - 29 Ohm
A2C53413384	white	105°F	250°F	none	none		287.4 – 22.7 Ohm
A2C53413388	white	105°F	250°F	40°C	120°C		287.4 – 22.7 Ohm
A2C53413403	white	120°F	300°F	none	none		322.8 – 18.6 Ohm
A2C53413407	white	120°F	300°F	50°C	150°C		322.8 – 18.6 Ohm

\* "No. unpacked" is not a order number.

**Accessories:**

A2C59510886	VL Make point switch 12V
A2C59510854	VL Mounting Kit (studs and brackets) 52, 85, 110mm
A2C53007398	Fastening nut
A2C59510864	VL Mounting bracket flush mount
A2C53215640	VL Sealing Ring 52mm flush mount
A2C59510847	Bush housing, 8-pin
A2C53324664	Protective connector cap, 8-pin
Tyco No. 539635-1	Hand pliers
Tyco No. 539682-2	Tool for hand pliers.
Tyco No. 1355718-1	Single contacts 0.14 – 0.22 mm <sup>2</sup> tin plated
Tyco No. 963729-1	Single contacts 0.5 – 0.75 mm <sup>2</sup> tin plated
Tyco No. 1355717-1	Strip 0.14 – 0.22 mm <sup>2</sup> tin plated
Tyco No. 928999-1	Strip 0.25 – 0.5 mm <sup>2</sup> tin plated
Tyco No. 963715-1	Strip 0.5 – 0.75 mm <sup>2</sup> tin plated

**Bezels 52mm**

	Black	Chrome	White
<b>Flat</b>	A2C53186040	A2C53186023	A2C53186022
<b>Round</b>	A2C53186027	A2C53186029	A2C53186028
<b>Triangle</b>	A2C53186024	A2C53186026	A2C53186025

